

Supplier's name or trade mark:	MEGAMAN GmbH
Supplier's address	Halskestraße 22-26, AircomParc A140880 RatingenGermany

Model identifier	SHB717v0840
Equivalent Models	N/A

#### Technical Document

Useful luminous flux	N/A
On-mode Power (P <sub>on</sub> )	N/A W
Beam angle in degrees for directional light sources (DLS)	N/A
Peak luminous intensity in cd for directional light sources (DLS)	N/A
Correlated Colour Temperature	N/A K
Chromaticity coordinates (x,y)	N/A, N/A
Colour Rendering Index (CRI)	Ra N/A
Standby Power (P <sub>sb</sub> )	N/A
Networked Standby Power (P <sub>net</sub> )	N/A
R9 colour rendering index value for LED and OLED light sources	N/A
Survival factor for LED and OLED light sources	N/A
Lumen maintenance factor for LED and OLED light sources	N/A
Indicative lifetime L70B50 for LED and OLED light sources	N/A
Displacement Factor (cos φ1)	N/A
Colour Consistency	SDCM ≤ N/A
Luminance for HLLS	N/A
Flicker metric (P <sub>stLM</sub> )	N/A
Stroboscopic effect metric (SVM)	N/A
Excitation purity for CTLS	N/A
Weighted Energy Consumption	N/A kWh/1000hrs
Energy Efficiency Class	N/A
Outer dimensions in mm	
Height	N/A
Width	N/A
Depth	N/A
Standards Compliance	CE, RoHS

#### CALCULATIONS - GENERAL RULE

Refer to Annex II of Energy Labelling (EU) 2019/2015

##### Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy  $\eta_{TM}$ , which is calculated by dividing the declared useful luminous flux  $\Phi_{use}$  (expressed in *lm*) by the declared on-mode power consumption  $P_{on}$  (expressed in *W*) and multiplying by the applicable factor FTM of Table 2, as follows:

$$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)}$$

Table 1

Energy efficiency classes of light sources	
Energy efficiency class	Total mains efficacy $\eta_{TM}$ (lm/W)
A	$210 \leq \eta_{TM}$
B	$185 \leq \eta_{TM} < 210$
C	$160 \leq \eta_{TM} < 185$
D	$135 \leq \eta_{TM} < 160$
E	$110 \leq \eta_{TM} < 135$
F	$85 \leq \eta_{TM} < 110$
G	$\eta_{TM} < 85$

Table 2

Factors FTM by light source type	
Light source type	Factor FTM

Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

#### ADDITIONAL PART

A list of compatible dimmers shall be provided on the website [www.megaman.cc](http://www.megaman.cc)

MEGAMAN | WEEE - Green Room | LED, Energy-efficient & Eco-friendly Lighting, Restriction of Hazardous Substances

<https://www.megaman.cc/resources/green-room/weee>

MEGAMAN GmbH  
Halskestraße 22-26, AircomParc A1  
40880 Ratingen  
Germany



Removable Light Source			
Model No.	Light Source Model identifier	Input Voltage (V)	Input Current (mA)
FHB71600v0	SHB716v0840	DC 118	789
FHB71700v0	SHB717v0840	DC 118	1180
FHB71800v0	SHB718v0840	DC 118	1570

Step1: Loosen the screw, Separate the driver module from fixture.



Step2: remove the lens



Step3: remove the Sensor holder



Step4: Loosen the sensor holder screw



Step5: cut out the wire



Step6: light source

