

Supplier's name or trade mark:	MEGAMAN GmbH
Supplier's address	Halskestraße 22-26, AircomParc A140880 RatingenGermany

Model identifier	STK700v0db828
Equivalent Models	N/A

Technical Document

Useful luminous flux	900
On-mode Power (P _{on})	10.8 W
Beam angle in degrees for directional light sources (DLS)	36
Peak luminous intensity in cd for directional light sources (DLS)	800
Correlated Colour Temperature	2800 K
Chromaticity coordinates (x,y)	0.454, 0.412
Colour Rendering Index (CRI)	Ra 80
Standby Power (P _{sb})	N/A
Networked Standby Power (P _{net})	N/A
R9 colour rendering index value for LED and OLED light sources	0
Survival factor for LED and OLED light sources	0.90
Lumen maintenance factor for LED and OLED light sources	0.96
Indicative lifetime L70B50 for LED and OLED light sources	25000
Displacement Factor (cos φ ₁)	0.9
Colour Consistency	SDCM ≤ 3
Luminance for HLLS	N/A
Flicker metric (P _{stLM})	N/A
Stroboscopic effect metric (SVM)	N/A
Excitation purity for CTLS	N/A
Weighted Energy Consumption	11 kWh/1000hrs
Energy Efficiency Class	G
Outer dimensions in mm	
Height	85
Width	50
Depth	50
Standards Compliance	CE, RoHS

CALCULATIONS - GENERAL RULE

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in *lm*) by the declared on-mode power consumption P_{on} (expressed in *W*) and multiplying by the applicable factor FTM of Table 2, as follows:

$$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)}$$

Table 1

Energy efficiency classes of light sources	
Energy efficiency class	Total mains efficacy η_{TM} (lm/W)
A	$210 \leq \eta_{TM}$
B	$185 \leq \eta_{TM} < 210$
C	$160 \leq \eta_{TM} < 185$
D	$135 \leq \eta_{TM} < 160$
E	$110 \leq \eta_{TM} < 135$
F	$85 \leq \eta_{TM} < 110$
G	$\eta_{TM} < 85$

Table 2

Factors FTM by light source type	
Light source type	Factor FTM

Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN | WEEE - Green Room | LED, Energy-efficient & Eco-friendly Lighting, Restriction of Hazardous Substances

<https://www.megaman.cc/resources/green-room/weee>

MEGAMAN GmbH
Halskestraße 22-26, AircomParc A1
40880 Ratingen
Germany








Model no.: FTK70000v0

Light source model identifier: STK700v0828, STK700v0840,

Light source: Removable

STK708v0830 I in: 300mA U in 36VDC

STK708v0840 I in: 300mA U in 36VDC

<p>Step1:whole fixtures</p> 	<p>Step2: Remove the cap</p> 	<p>Step3: loose the screws</p> 
<p>Step4: take out the adaptor and cut down the wires</p> 	<p>Step5: take out the driver and cut down the wires</p> 	<p>Step6: Light source</p> 