T8 - Magnetic/AC Mains



LT205180/mb-12v02+G13+865+V0240



18W G13 1800lm 6500K Ra80 1200mm

GENERAL DESCRIPTION

Model Number	LT205180/mb-12v02
Product Code	LT205180/mb-12v02+G13+865+V0240
Model Identifier	711835/MM11835-1
Cap Base	G13
Dimmable	No
Working Temperature	-30°C to +45°C

TECHNICAL PARAMETERS

LIFE PERFORMANCE

Indicative Lifetime L70B50 (hrs)	15000	at 25°C
Number of Switching Cycles	> 100000	

ELECTRICAL DATA

ELECTRICAL DATA		
On-mode Power (W)	18	
Input Voltage	220-240 VAC	
Frequency	50/60 Hz	
Displacement Factor (cos φ1)	0.70	
Equivalent Power (W)	N/A	
Standby Power (W)	0.0	
Networked Standby Power (W)	N/A	
Survival Factor	0.90	
Lumen Maintenance Factor	0.93	

PHOTOMETRIC INFORMATION

Useful Luminous Flux (Im)	1800	
Useful Luminous Flux in 90° Cone (Im)	N/A	
Useful Luminous Flux in 120° Cone (Im)	N/A	
Correlated Colour Temperature (K)	6500	
Colour Consistency	6	
Colour Rendering Index	80	
R9 Colour Rendering Index Value	0	
Beam Angle (°)	N/A	
Peak Luminous Intensity (cd)	N/A	
Stroboscopic Effect Metric (SVM)	0.4	
Flicker Metric (P _{st} ^{LM})	1.0	
Chromaticity Coordinates (x and y)	0.315	
	0.345	

ENERGY EFFICIENCY

Weighted Energy Consumption (kWh/1000hrs)	18
Energy Class	F

CERTIFICATES & STANDARDS

Standards Compliance	IEC/EN 62776, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3
Approvals	CE, RoHS

DIMENSIONS & WEIGHT

Height (mm)	1212
Width (mm)	28
Depth (mm)	28
Weight (g)	210

T8 - Magnetic/AC Mains

LED Tubes

LT205180/mb-12v02+G13+865+V0240



18W G13 1800lm 6500K Ra80 1200mm

SPECIFIC PRECAUTIONS - GENERAL GUIDELINES



Dimming not allowed





Lamp suitable for dimming only with specific dimmers (A list of compatible dimmers shall be provided on the website www.megaman.cc)





Lamp not suitable for use under dust and moisture

Indoor use only

Turn off the lamp and let it cool down before any replacement

Do not run LED and incandescent lights on a trailer

For lamps with a weight significantly higher than that of the lamps for which they are a replacement, attention should be drawn to the fact that the increased weight may reduce the mechanical stability of certain luminaires and lamp holders and may impair contact making and lamp retention.

TESTING CONDITIONS

Refer to Annex A of IEC 62612 method of measuring lamp characteristics Light output and life hour are measured at 25°C, 230V

T8 - Magnetic/AC Mains

LED Tubes

LT205180/mb-12v02+G13+865+V0240



18W G13 1800lm 6500K Ra80 1200mm

CALCULATIONS - GENERAL RULES

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in lm) by the declared on-mode power consumption P_{on} (expressed in W) and multiplying by the applicable factor FTM of Table 2, as follows:

 $\eta TM = (\Phi use/Pon) \times FTM (Im/W)$

Table 1
Energy efficiency classes of light sources

Energy enforcing diases of light sources		
Energy efficiency class	Total mains efficacy ηTM (lm/W)	
A	210 ≤ ηTM	
В	185 ≤ ηTM < 210	
С	160 ≤ ηTM < 185	
D	135 ≤ ηTM < 160	
E	110 ≤ ηTM < 135	
F	85 ≤ ηTM < 110	
G	ηTM < 85	

Table 2
Factors FTM by light source type

ractors rim by light source type		
Light source type	Factor FTM	
Non-directional (NDLS) operating on mains (MLS)	1,000	
Non-directional (NDLS) not operating on mains (NMLS)	0,926	
Directional (DLS) operating on mains (MLS)	1,176	
Directional (DLS) not operating on mains (NMLS)	1,089	

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN GmbH Halskestraße 22-26, AircomParc A1 40880 Ratingen Germany



 $\ensuremath{\text{@}}$ Copyright 2021. All rights reserved by MEGAMAN $\ensuremath{\text{@}}$

30/1/2024